Wheatit



heatit

PRODUCT INFO Heatit WiFi

FEATURES

- Floor sensor or external sensor
- Internal room sensor
- Power regulator
- Adaptive regulation
- Temperature limiter
- Weekly schedule
- Home/Away/Anti-frost
- Intuitive app easy to use
- Control via app

TECHNICAL DATA

- Alarm/notifications in app
- Firmware update (OTA)
- Energy calculator
- Single pole switch
- Lock mode/Child lock
- CalibrationAmazon Cloud
- Norwegian/Swedish/
 - English/Finnish/Dutch languages

Protocol	WiFi 2.4GHz 802.11bgn	
Display	1.8"TFT, 128x160 resolution	
Rated voltage	230VAC 50Hz	
Max load	3600W (only resistive loads)	
	Use contactor for loads higher than 13A	
Max current	16A	
Power consumption	<2W	
Ambient temperature	5°C to 40°C (during operation)	
Temperature range	5°C to 40°C	
Hysteresis	0.2°C to 2°C (0.5°C standard)	
Compatible with NTC		
sensors with values	6.8, 10, 12, 15, 22, 33, 47, 100 kΩ @ 25°C	
IP Code	IP 21	
Approvals	CE	

Approved for use in bathrooms.

TERMINAL Use 1.5mm² or 2.5mm² according to load.

MAINTENANCE

The device is maintenance-free, but must never be covered. Only for indoor installation.

WARRANTY

2 years

ART. NO.	PRODUCT	COLOR	FREQUENCY
54 305 89	Heatit WiFi thermostat 3600W 16A	White RAL 9003	WiFi 2.4GHz
54 305 88	Heatit WiFi thermostat 3600W 16A	Black	WiFi 2.4GHz
54 301 31	Heatit External Room Sensor NTC 10k Ω	White RAL 9003	




- a smart WiFi thermostat



Heatit WiFi is an electronic thermostat for electrical underfloor heating, designet to be mounted in a standard flush box. The thermostat has a simple user interface and can be easily programmed via the capacitive buttons. The color screen displays an accessible user interface.

The thermostat has a built-in WiFi chip that allows you to control it from a user-friendly app. The "Heatit WiFi" app is available on Google Play and in the App Store. Works with Amazon Alexa and Google Home. If you are installing multiple thermostats in the same house, you may copy the settings from one thermostat to the next. This simplifies installation.

Heatit WiFi Thermostat is equipped with a single-pole switch and fits into System 55 frames. The thermostat can withstand a load of max 16A/3600W at 230VAC. We recommend a contactor for loads above 13A. The thermostat may be connected to an wired external sensor.









Heatit Controls AB can not be held liable for typographical errors, other errors or omittances in our information. Product specifications may change without further notice. Warranty does not apply to batteries

heatit.com