

40m

Yes

25A



PRODUCT FEATURES

- Multifunction relay
- Calibration
- · Many different uses
- Associations
- Marry afficient ase
- Firmware update (OTA)

• 3 inputs

• 25A

- Power metering
- · Option of external antenna
- Can be used with different types of NTC sensors
- Multilevel sensor command class
- Supports encryption mode S0, S2 Authenticated Class, S2 Unauthenticated Class

				TΑ

Ambient temperature range in use	-20 to 40°C		
Colour	White RAL 9010		

THERMOSTAT DATA

Compatible NTC-sensors (k Ω @ 10, 12, 15, 22, 33, 47 25°C)

ADDITIONAL INFO IP Code IP55 Certification Reach, RoHS Warranty international 2 years Customs number 90321000 Country of origin EE

HEATIT Z-RELAY 25A IP55

Z-Wave Relay 25A 868,4 MHz

Art.no 4512554

GTIN 7071236014522

Heatit Z-Relay multipurpose relay module may be used for many different applications. The IP 55 rated casing makes it useful for any outdoor application. Can pull loads up to 25A. The relay has 3 inputs.

Heatit Z-Relay is a multipurpose product and may be used for the following applications:

- Leakage control
- Varied outdoor applications

Min radio frequency range

Over The Air update (OTA)

Max load (resistive load)

IOT / SMART HOME SPECIFIC DATA

Primary IoT Protocol	Z-Wave
Z-Wave Frequency	Z-Wave - 868.4 MHz (EU)
Z-Wave Chip	Z-Wave 500 chip
Z-Wave encryption mode	S2 Unauthenticated Class
	S2 Authenticated Class
	S0

ELECTRO TECHNICAL DATA				
Voltage	230VAC 50Hz			
Voltage Output	230VAC 50Hz			
Own power usage	0.8W			
Max load (resistive load)	5750W			













PRODUCT DIMENSIONS						
Product height/diameter	50mm	Product Width	180mm			
Product length	210mm	Product net weight	224g			

MAINTENANCE

The product is maintenance-free.

ADDITIONAL INFORMATION

This product is a security-enabled Z-Wave Plus product with encryption. The product must be used with a security-enabled Z-Wave Controller in order to fully utilize the product.

Standards: CE, EMC 2014/30/EU, EN 50491-3:2009, EN 60669-2: 2004, LVD 2014/35/EU, RoHS 2011/65/EU, Z-Wave Plus

RETURN AND RECYCLING

The product must be recycled as electronic waste.

DISCLAIMER

We develop and design our products according in accordance with our strict quality requirements (ISO 9001) and environmental requirements (ISO 14001).

All electrical installations must be carried out by an authorized electrical installer. The product must be installed in accordance with our installers manual and national building codes. Any wrongful installation, misuse, damage of the product, is not covered under warranty.

Updated documentation is available at www.heatit.com and/or documents.heatit.com
Heatit Controls AS can not be held liable for any type of errors or omittances in our product information.
Product specifications may change without further notice.














Heatit Z-Relay 25A IP55 can be ordered from www.heatit.com/4512554



All additional documentation are available on the above adress and on documents.heatit.com/4512554







