







Overload protection

Surge protection

Overheat protection

Two external switchesMin. dim level adjustable

On/off functionality

• Short circuit protection

PRODUCT FEATURES

- Z-Wave
- 2 or 3-wire
- 5W 250W
- LED, incandescent and halogen
- SmartStart
- Scene controller
- Firmware update (OTA)
- Active power metering
- Dimmer for inwall installations
- · Max. dim level auto-calibration
- Supports encryption mode S0, S2 Authenticated Class, S2 Unauthenticated Class

PRODUCT DATA	
Colour	Black Olive RAL 6015
Min. and max ambient humidity (RH%)	10 to 85%
Ambient temperature range in use	5 to 40°C
Ambient temperature range in storage	-30 to 70°C

STANDARDS	
Certification	Reach, RoHS
IP Code	IP20
WARRANTY	

HEATIT ZM DIMMER 250W

Inwall Z-Wave Dimmer

Art.no 1444449

GTIN 7071236018575

Smart dimmer

Heatit ZM Dimmer is a 250W dimmer suitable for use with LED lights and other types of light sources. The dimmer works with most low loads without causing flicker. The dimmer enables the user to control light sources from the Z-Wave network and/or an external switch. Heatit ZM Dimmer is an inwall dimmer for installation in European electrical wall boxes

The Heatit ZM Dimmer works on most low loads of both LEDs and other light fixtures without causing flickering.

The dimmer has 2 switch inputs that, in addition to controlling the dimmer, can be used as scene controllers.

The dimmer can be wirelessly connected to other devices via associations.

Heatit ZM Dimmer features active power metering, providing real-time information about your power consumption.

IOT / CMADT HOME CDECIEIC DATA

IOT / SMART HOME SPECIFIC DATA		
Z-Wave Frequency	Z-Wave - 868.4 MHz (EU)	
Z-Wave Chip	Z-Wave 800 chip	
Min radio frequency range	40m	
Over The Air update (OTA)	Yes	
Push buttons	2	
Z-Wave encryption mode	S2 Unauthenticated Class S0	
	S2 Authenticated Class	
Primary IoT Protocol	Z-Wave	

Voltage	230VAC 50Hz
Own power usage	1W
Power	5 to 250W
Connection type	Screw clamps
Connection terminals diameter	0.2 to 2.5mm ²
Max tightening torque connections	2N·m
Voltage Output	230VAC 50Hz
Grounding	No



Warranty international



2 years













	PRC	DU	CT	DIME	NSIONS
--	------------	-----------	----	------	--------

Product height/diameter	21mm	Product Width	45mm
Product length	46mm	Product net weight	37g

MAINTENANCE

The device is maintenance-free. Indoor use only.

ADDITIONAL INFORMATION

The product must be used with a security-enabled Z-Wave Controller in order to fully utilize security/encryption.

Dimming may be challenging, and we recommend checking the compatibility of different light sources before installation.

When connecting low loads it is recommended to use a bypass.

PRODUCT INFO RETURN AND RECYCLING

The product must be recycled as electronic waste.

DISCLAIMER

We develop and design our products according in accordance with our strict quality requirements (ISO 9001) and environmental requirements (ISO 14001).

All electrical installations must be carried out by an authorized electrical installer. The product must be installed in accordance with our installers manual and national building codes. Any wrongful installation, misuse, damage of the product, is not covered under warranty.

Updated documentation is available at www.heatit.com and/or documents.heatit.com

Heatit Controls AB can not be held liable for any type of errors or omittances in our product information.

Product specifications may change without further notice.






























Document generated 30. Mar 2025 kl. 16:44



Heatit ZM Dimmer 250W can be ordered from www.heatit.com/1444449

All additional documentation are available on the above adress and on **documents.heatit.com/1444449**











