



FOSCAM DOME CAMERA

EOL

IP Camera outdoor use

Art.no 4512417
GTIN 6954836086254

The Foscam Dome Camera is a compact surveillance camera designed for outdoor use. The camera features 1080p HD resolution, allowing it to capture clear images even in challenging lighting conditions. Its wide viewing angle and smart human detection capability make it an excellent choice for outdoor surveillance of residential and commercial spaces.

The Foscam Dome Camera comes with Power over Ethernet (PoE) instead of Wi-Fi. This means the camera can receive power through the network cable, eliminating the need for a power outlet where the camera is installed. Of course, it's also possible to connect the camera to power using the included power adapter.

The Foscam Dome Camera has a slot for a Micro SD memory card. You can store videos on this memory card and play them back later by logging into the camera through a web browser.

The IR-Cut filter allows the camera to automatically switch between day and night modes. During the daytime, the camera is set to consider lighting conditions to provide sharp, natural images, while at night, it focuses on maximizing the use of limited light. At night, the automatic IR LEDs also activate, allowing the camera to interpret incoming data as if the outdoor area were illuminated.

The Foscam Dome Camera is designed for outdoor ceiling mounting but can also be used indoors, of course. The camera has an IK10 certification, which means it is built to withstand vandalism.

The camera's angle can be adjusted to cover the desired area. All adjustments must be made manually since the camera is not motorized.

PRODUCT FEATURES

- Outdoor surveillance camera
- Connects to the network using a network cable
- Approximately 110-degree field of view
- Sees in complete darkness with IR light with a range of up to 20 meters
- Vandal-resistant casing
- Supports Micro SD memory card (up to 64GB)
- HD resolution 1080P 1920x1080
- IR-cut filter for optimal image with true colors in daylight
- H.264 protocol for reduced bandwidth usage
- Audio input/output for connecting to a microphone/speaker
- Magic Zoom
- WDR 2.0 technology for the best possible image quality in challenging lighting conditions

ELECTRO TECHNICAL DATA

Voltage	230V-12V
Own power usage	4.5W



MAINTENANCE

The device is maintenance-free.

PRODUCT INFO RETURN AND RECYCLING

The product must be recycled as electronic waste.

STANDARDS

EN Standards	CE	Certification	CE
IP Code	IP66		

WARRANTY

Warranty Norway	2 years
-----------------	---------

LOGISTICAL DATA (F-PACK)

Width	115mm	Height/diameter	185mm
Length	170mm	Weight	1030g
GTIN	6954836086254	Unit	EA
Consists of unit	EA	Quantity	1

DISCLAIMER

All electrical installations must be carried out by an authorized electrical installer. The product must be installed in accordance with our installers manual and national building codes. Any wrongful installation, misuse, damage of the product, is not covered under warranty.

Updated documentation is available at www.thermo-floor.no/www.heatit.com og/eller documents.thermo-floor.no/documents.heatit.com Thermo-Floor AS/Heatit Controls AB can not be held liable for any type of errors or omissions in our product information. Product specifications may change without further notice.





Foscam Dome Camera can be ordered from www.thermo-floor.no/4512417

All additional documentation are available on the above adress and on documents.thermo-floor.no/4512417

