



PRODUCT FEATURES

• M 30x1.5

Valve test.

· Open/Close indicator.

- Manual opening function.
- NC Normally closed.
- 360° installation position.

Silent.

- Made in EU.
- Electrothermal actuator (telestat) for energy-efficient control of waterbased heating and cooling systems.
- Energy-efficient thanks to a low power consumption.
- Simple installation without tool.
- Compact design, low dimensions.
- · High functional reliability and long life.
- Durable and reliable high-quality materials.
- Tested quality confirmed by the TÜV Rheinland according to the IEC 60730-2-14.

| PR | ^ | | п | | ГГ | 7 | т. | Λ |
|----|---|---|---|---|----|----|-----|---|
| ΓN | v | v | u | L | L | JH | \ I | н |

Colour Black Olive RAL 6015

| STANDARDS | | |
|---------------|------|--|
| Certification | CE | |
| IP Code | IP54 | |

HEATIT ACTUATOR 230VAC

Actuator for waterbased heating systems

Art.no 4590030

GTIN 7071236018964

Compact electrothermal actuator for controlling waterbased heating systems. Can be regulated manually or on a signal from a thermostat or external regulator.

ELECTRO TECHNICAL DATA

| Voltage | 230VAC 50/60Hz |
|-------------------|----------------|
| Own power usage | 1W |
| Operating power | 8mA |
| Max start current | 300mA |









| PRODUCT DIMENSIONS | | | | | | |
|-------------------------|------|--------------------|------|--|--|--|
| Product height/diameter | 75mm | Product Width | 37mm | | | |
| Product length | 43mm | Product net weight | 113g | | | |

MAINTENANCE

Cable must not be removed. The actuator must not be disassembled or opened! Otherwise maintenance-free.

PRODUCT INFO RETURN AND RECYCLING

The product must be recycled as electronic waste.

DISCLAIMER

We develop and design our products according in accordance with our strict quality requirements (ISO 9001) and environmental requirements (ISO 14001).

All electrical installations must be carried out by an authorized electrical installer. The product must be installed in accordance with our installers manual and national building codes. Any wrongful installation, misuse, damage of the product, is not covered under warranty.

Updated documentation is available at www.heatit.com and/or documents.heatit.com
Heatit Controls AB can not be held liable for any type of errors or omittances in our product information.
Product specifications may change without further notice.









Heatit Actuator 230VAC can be ordered from www.heatit.com/4590030

All additional documentation are available on the above adress and on **documents.heatit.com/4590030**





