



## TF STICKY MAT 60W/M<sup>2</sup>

Self-adhesive heating cable mat for embedment

TF Sticky Mat is a low build-up, twin conductor grounded heating mat for embedment. The build-up ranges from 4 - 20mm depending on the underlay and floor covering. TF Sticky Mat has a heating cable (Ø 3,2mm) placed in a serpentine pattern with 80mm space between the heating cables.

TF Sticky Mat is self-adhesive.

The sub-floor must be clean, even and primed. Roll out the TF Sticky Mat and adjust it to the desired area. The adhesive on the net sticks easily to the subfloor. TF Sticky Mat may be installed directly on wood, chipboard, concrete e.g. The heating mat must be covered with screed.

Available in four effect variants: 60W/m<sup>2</sup>, 100W/m<sup>2</sup>, 130W/m<sup>2</sup>, and 160W/m<sup>2</sup>.

### PRODUCT FEATURES

- TF Sticky Mat can be installed underneath tiles, parquet, laminate, carpets, cork flooring and practically all other floors that may be heated.
- TF Sticky Mat can be placed directly onto flammable materials.

### PRODUCT COVER

Carpet floor, Concrete, Cork, Flooring, Laminate floors, Parquet floors, Tiles, Vinyl, Woodchip boards

Always install TF Sticky Mat in accordance with the manual. Please observe that in wet areas, a membrane should always be placed beneath the tile adhesive to ensure that only the tiles, tile adhesive and grout comes in contact with water.

### GROUND PROTECTION/RCD/THERMOSTAT

The heating system must be equipped with an RCD with a maximum trip value of 30mA.

The heating system must be installed with an electronic thermostat for energy efficiency and temperature control.

### PRODUCT DATA

|  |                          |
|--|--------------------------|
| Voltage  | 230VAC 50Hz              |
| Cable type   | Twin conductor, grounded |
| Effect per m <sup>2</sup> (watt per m <sup>2</sup> ) | 60W                      |
| Cable diameter (Ø - mm)                              | 3.2mm                    |
| Cold lead  | 5m                       |
| Max temperature (average)                            | 80°C                     |
| Ambient temperature range in use                     | 0 to 40°C                |
| Min/max installation temperature                     | 0 to 40°C                |
| Colour   | Red                      |
| IP Code  | IPX7                     |
| Certification  | EN 50575, Reach, RoHS    |
| EN Standards   | CE, EN 60335             |
| Warranty international                               | 2 years                  |
| Customs number                                       | 85168000                 |



**Product Overview**

| Art no.   | Product                                 | Size      | Total effect | Areal             | Ohm-value |  |
|-----------|---|-----------|--------------|-------------------|-----------|--|
| 10 115 04 | TF Sticky Mat 60W/4m <sup>2</sup> 240W  | 0.5 x 8m  | 240W         | 4 m <sup>2</sup>  | 220 Ω     |  |
| 10 115 05 | TF Sticky Mat 60W/5m <sup>2</sup> 300W  | 0.5 x 10m | 300W         | 5 m <sup>2</sup>  | 176 Ω     |  |
| 10 115 06 | TF Sticky Mat 60W/6m <sup>2</sup> 360W  | 0.5 x 12m | 360W         | 6 m <sup>2</sup>  | 146 Ω     |  |
| 10 115 07 | TF Sticky Mat 60W/7m <sup>2</sup> 420W  | 0.5 x 14m | 420W         | 7 m <sup>2</sup>  | 125 Ω     |  |
| 10 115 08 | TF Sticky Mat 60W/8m <sup>2</sup> 480W  | 0.5 x 16m | 480W         | 8 m <sup>2</sup>  | 110 Ω     |  |
| 10 115 09 | TF Sticky Mat 60W/9m <sup>2</sup> 540W  | 0.5 x 18m | 540W         | 9 m <sup>2</sup>  | 98 Ω      |  |
| 10 115 10 | TF Sticky Mat 60W/10m <sup>2</sup> 600W | 0.5 x 20m | 600W         | 10 m <sup>2</sup> | 88 Ω      |  |
| 10 115 12 | TF Sticky Mat 60W/12m <sup>2</sup> 720W | 0.5 x 24m | 720W         | 12 m <sup>2</sup> | 73 Ω      |  |

**MAINTENANCE**

The product is maintenance-free, but it must always be installed in compliance with the manual.

**RETURN AND RECYCLING**

The product must be recycled as electronic waste.

**PRODUKT DATA**

|                                  |  |                                  |            |
|----------------------------------|--|----------------------------------|------------|
| Covering                         | Carpet floor<br>Laminate floors<br>Vinyl<br>Concrete<br>Woodchip boards<br>Parquet floors<br>Tiles<br>Flooring<br>Cork | Colour                           | Red        |
| Outer sleeve material            | Polyvinylechloride (PVC)   | Ambient temperature range in use | 0 til 40°C |
| Min/max installation temperature | 0 til 40°C   |                                  |            |

**DISCLAIMER**

We develop and design our products according in accordance with our strict quality requirements (ISO 9001) and environmental requirements (ISO 14001).  
 All electrical installations must be carried out by an authorized electrical installer. The product must be installed in accordance with our installers manual and national building codes. Any wrongful installation, misuse, damage of the product, is not covered under warranty.  
 Updated documentation is available at [www.thermo-floor.no](http://www.thermo-floor.no) and/or [documents.thermo-floor.no](http://documents.thermo-floor.no)  
 Thermo-Floor AS can not be held liable for any type of errors or omissions in our product information.  
 Product specifications may change without further notice.



## TF Sticky Mat 60W/m<sup>2</sup> can be ordered from thermo-floor.no

All additional documentation are available on [documents.thermo-floor.no/10115-01](https://documents.thermo-floor.no/10115-01)

