




Document generated 11. Feb 2025 kl. 16:15





#### **PRODUCT FEATURES**

- · Frees up floor and wall space.
- Suitable for both spot heating and overall heating.
- · Easy installation and flexible placement.
- Provides quick heat where needed.

# HEATIT RCH HEATING PANEL WHITE 119X60CM 600W WAGO

Radiant Ceiling Heating Panel

**Art.no** 5430443

**GTIN** 7071236019565

Heatit Radiant Ceiling Heating panel (RCH) - electrical radiant heating is a product suitable for both total and local heating. Radiant heating panels can be installed in suspended ceilings or directly in the ceiling. The product is well-suited for both overall heating and local heating. When the heating panels are installed in a suspended ceiling, they are well-protected against damage and can be easily moved when needed. Ceiling installation frees up the walls and increases safety. The heating panel is splash-proof and approved for use in wet rooms. Heatit radiant ceiling heating panel also provides excellent protection against cold drafts from window surfaces.

Spot heating ensures individual comfort at, for example, office desks and workstations. Radiant heating works by warming up objects that the rays hit. Heatit Radiant Ceiling Heating panel provides immediate warmth, and room temperature can be lowered without compromising comfort. There is no need to start heating more than 30 to 60 minutes before the workday starts, and the heat can be turned off when the workday ends. This reduces heating costs while being energy-efficient compared to traditional heating.

Heatit Radiant Seiling Heating panel in commercial buildings is a natural and forward-looking choice for those who need to heat large areas or rooms that are not in continuous use.

Supplied with Wago WINSTA® MIDI, plug 3-poled. Art no: 770-113.

Voltage	230VAC 50Hz	
Grounding	Yes	
Total gross effect	600W	
Cold lead	5m	
Mounting height	1.8 to 4m	
Ambient temperature range in use	5 to 40°C	
Ambient temperature range in storage (°C)	-30 to 70°C	
Min/max installation temperature	5 to 40°C	
Min. and max ambient humidity (RH%)	10 to 85%	
Material	Steel	
Colour	White RAL 9003	
Mounting	Mounted using bracket to roof or wall, System Ceiling, T-system	
IP Code	IP55	
Certification	Reach, RoHS	
EN Standards	CE, Semko	
Warranty international	2 years	
Customs number	85162902	











## **PRODUCT DIMENSIONS**

Product height/diameter	45mm	Product Width	595mm
Product length	1190mm	Product net weight	13800g

### **MAINTENANCE**

Heatit Radiant Ceiling Heating is maintenance-free, but it must always be installed in compliance with the manual.

## **ADDITIONAL INFORMATION**

Supplied with 5m cold lead.

#### PRODUCT INFO RETURN AND RECYCLING

The product must be recycled as electronic waste.

#### **DISCLAIMER**

Min. installation height: 1.8 meters. Max. installation height: 4.0 meters.

Galvanized and powder-coated steel plate.

Supplied with 5m cold lead.

We develop and design our products according in accordance with our strict quality requirements (ISO 9001) and environmental requirements (ISO 14001).

All electrical installations must be carried out by an authorized electrical installer. The product must be installed in accordance with our installers manual and national building codes. Any wrongful installation, misuse, damage of the product, is not covered under warranty.

Updated documentation is available at www.heatit.com and/or documents.heatit.com

Heatit Controls AB can not be held liable for any type of errors or omittances in our product information.

Product specifications may change without further notice.











# Heatit RCH Heating Panel White 119x60cm 600W WAGO can be ordered from www.heatit.com/5430443

All additional documentation are available on the above adress and on documents.heatit.com/5430443



