



TF SBG-H RED

Self limiting heating cable for use in environments with high temperatures 200°C

TF SBG-H is a self-limiting heating cable designed for use in high temperature environments.

The heating cable is suitable for frost protection, but can also be used to maintain a constant temperature on pipes, taps and containers. Although the product has many uses, it is mostly used in the chemical and petrochemical industries. TF SBG-H is available in several effects. With a fluoropolymer outer sheath, better known as Teflon, the product is well suited for use with aggressive chemicals, oils, gasoline and diesel. The product is UV-resistant. TF SBG-H is approved for use in potentially explosive atmospheres and can be used at temperatures up to 200°C.

PRODUCT FEATURES

- For use in environments with high temperatures.

GROUND PROTECTION/RCD/THERMOSTAT

The heating system must be equipped with an RCD with a maximum trip value of 30mA.

The heating system must be installed with an electronic thermostat for energy efficiency and temperature control.

PRODUCT DATA

Voltage	230VAC
Cable type	Self limiting heating cable
Grounding	Braided, tinned copper wires
Bus conductor	Nickel Coated Copper Wire
Max temperature without load	200°C
Max temperature with load	120°C
Min bend radius (mm)	25mm
Weight per meter (gram)	118g
Min/max installation temperature	-45 to 30°C
Colour	Red
Outer sleeve material	Fluoropolymer
IP Code	IPX7
Certification	Reach, RoHS
EN Standards	CE, EN 60079, EN 60529
Warranty Norway	5 years
Warranty international	2 years
Product height/diameter	4.3mm
Product Width	11.5mm
Product length	1000mm
Customs number	85459000



Product Overview

Art no.	Product	Effect per m.	
10 113 31	TF SBG-H Red 10W/m	10W	
10 113 32	TF SBG-H Red 20W/m	20W	
10 113 33	TF SBG-H Red 30W/m	30W	
10 113 34	TF SBG-H Red 45W/m	45W	
10 113 36	TF SBG-H Red 60W/m	60W	

ADDITIONAL INFORMATION

In the Nordic climate, insulation will not be sufficient for full frost protection of pipes. Tough weather conditions with wind and cold can lead to frozen water pipes, sprinkler systems etc.

Self-limiting heating cables are built up with a temperature-dependent resistance element between two parallel copper conductors. When the self-limiting heating cable is connected to the mains voltage, the current will pass through the temperature-dependent resistance element, which is heated. When the element heats up, the resistance value rises. As a result, power consumption and heat fall again. This is what we call a self-limiting effect. This regulation of the power takes place anywhere on the cable and is adapted to the current ambient temperature.

Self-limiting heating cables have a high starting current depending on length and temperature. Fuses with C-characteristics must therefore always be used.

Special lengths with attached cold lead can be made to order.

The cable can be cut to the desired length.

MAINTENANCE

The product is maintenance-free, but it must always be installed in compliance with the manual. The product should be checked and tested annually.

RETURN AND RECYCLING

The product must be recycled as electric waste.

DISCLAIMER

Prerequisites:

230VAC nominal voltage.

Delayed circuit breakers with (C-type) max load 80%.

Max 10% voltage drop on bus conductors.

The self-limiting heating cable can be cut to the desired length.

We develop and design our products according in accordance with our strict quality requirements (ISO 9001) and environmental requirements (ISO 14001).

All electrical installations must be carried out by an authorized electrical installer. The product must be installed in accordance with our installers manual and national building codes. Any wrongful installation, misuse, damage of the product, is not covered under warranty.

Updated documentation is available at www.thermo-floor.no and/or documents.thermo-floor.no

Heatit Controls AS can not be held liable for any type of errors or omissions in our product information.

Product specifications may change without further notice.

