



MULTIREG LCD2 - WHITE RAL9010

Thermostat for indoor heating

Art.no 5430301
GTIN 7071236008309

Multireg LCD2 is an electronic thermostat for mounting in a standard wall box. Multireg LCD2 is equipped with a two-pole break and fits into most systems used in Norway (Elko RS16, Schneider Exxact, Eljo Trend and Norvesco).

PRODUCT FEATURES

- Room sensor
- Floor sensor
- Temperature limiter
- Power regulator
- Weekly program / night sink
- The thermostat comes delivered with floor sensor (Article no 54 301 07)
- Absence function
- Lock / Child lock
- Backlight
- Calibration

PRODUCT DATA

| | |
|-------------------------------------|----------------|
| Colour | White RAL 9010 |
| Min. and max ambient humidity (RH%) | 10 to 85% |
| Ambient temperature range in use | 0 to 60°C |

THERMOSTAT DATA

| | |
|------------------------------------|--------------------------|
| Compatible NTC-sensors (kΩ @ 25°C) | 10, 12, 15, 22, 33, 47 |
| Power regulator | Timed cycle 0-30 minutes |
| Error margin temperature | 0,5 |
| Hysteresis | ±0,5 |
| Ohm value at 25°C | 10kΩ |
| Max length of NTC sensor | 50m |
| Regulation temperature | 5 to 40°C |

STANDARDS

| | |
|---------------|------|
| Certification | CE |
| IP Code | IP21 |

WARRANTY

ELECTRO TECHNICAL DATA

| | |
|-----------------------------------|---------------------------|
| Voltage | 230VAC 50Hz |
| Max load (resistive load) | 3600W |
| Own power usage | 0.5W |
| Switch type | Two-pole switch |
| Max load (resistive load) | 16A |
| Connection type | Screw clamps |
| Connection terminals diameter | 0.2 to 2.5mm ² |
| Max tightening torque connections | 2N·m |
| Voltage Output | 230VAC 50Hz |



PRODUCT DIMENSIONS

| | | | |
|-------------------------|-------|--------------------|-------|
| Product height/diameter | 80mm | Product Width | 120mm |
| Product length | 110mm | Product net weight | 210g |

MAINTENANCE

The device is maintenance-free. Indoor use only.

ADDITIONAL INFORMATION

Coupling rail
Use 1.5mm² or 2.5mm² depending on power requirements.

Can be delivered to order with Eljo front and frame.

PRODUCT INFO RETURN AND RECYCLING

The product must be recycled as electronic waste.

DISCLAIMER

General info;

Worth noting regarding correct installation of thermostats.

When two or more thermostats are mounted too close to each other, the heat they emit, can interfere with the temperature sensors and the temperature in the junction box becomes too high. This can cause inaccurate temperature readings, especially under high load, leading to incorrect heating control. To avoid such issues, thermostats should be installed as far apart as possible and always in separate junction boxes. This ensures more accurate temperature readings.

In multi-frames with multiple units, the thermostat should always be mounted at the bottom, and no more than one thermostat should ever be installed in a multi-frame.

We develop and design our products according in accordance with our strict quality requirements (ISO 9001) and environmental requirements (ISO 14001).

All electrical installations must be carried out by an authorized electrical installer. The product must be installed in accordance with our installers manual and national building codes. Any wrongful installation, misuse, damage of the product, is not covered under warranty.

Updated documentation is available at www.thermo-floor.no and/or documents.thermo-floor.no

Thermo-Floor AS can not be held liable for any type of errors or omissions in our product information.

Product specifications may change without further notice.



**Multireg LCD2 - White RAL9010 can be ordered from
www.thermo-floor.no/5430301**

All additional documentation are available on the above adress and on documents.thermo-floor.no/5430301

