

HEATIT WIFI PANEL HEATER 1500W BLACK STEEL 1000X430MM

Electrical Radiator WiFi

Art.no	5430438
GTIN	7071236019084

Smart panel heater. The Heatit WiFi Panel Heater combines modern design with efficient, comfortable heating. Easily connect it to your Wi-Fi network and take control with the "MyHeatit" App. Turn the heater on or off, adjust the temperature, change heating modes, and monitor energy consumption directly from your smartphone – even when you're away. You can also control the heater using the physical buttons on top or integrate it with other systems through its open API over Wi-Fi.

Heatit WiFi Panel Heater has 2 modes; Heat and Eco.

Heatit WiFi Panel Heater has a modern, slim design and is aesthetically pleasing. Produced with the front in either steel or glass. It is easy to install and mount on the wall with the supplied bracket. The panel heater can also be mounted on metal feet, sold separately (Art. no. 54 305 12). The panel heater has a built-in tip-over protection that automatically disconnects the power if it tips over.

Heatit WiFi Panel Heater is a low-temperature panel heater with a maximum surface temperature of 58°C, designed for environments where safety and comfort are important. The low surface temperature makes it particularly suitable for kindergartens, schools and other areas where children and many people are present.

With an IP24 rating, the Heatit WiFi Panel Heater is suitable for use in bathrooms and wet rooms. The heater combines safe and comfortable heating with a modern design and smart control via Wi-Fi.

The output power can be adjusted from the menu or from the app. It has child lock and open window detection. The device has an open API and supports Amazon Alexa and Google Home.

The installer can configure the device via Bluetooth. After the devicve is set up, the installer can add the property to the customer. The customer can then transfer the device to their local Wi-Fi network.

Heatit WiFi Panel Heater has active power metering and it gives you real time information about your power consumption.

Heatit WiFi Panel Heaters come in two versions: traditional convectors and skirting panel heaters. Traditional convectors are available in steel or glass, while skirting panel heaters are offered in steel only. The heaters are available in outputs from 400W up to 1500W and in white or black, depending on the model.

PRODUCT FEATURES

- Wi-Fi (2.4GHz)/BLE
- Open API for integration
- Digital thermostat
- Silent control Triac
- Easy-to-read LCD display
- Two modes: Heat and Eco-mode
- Active power metering
- Open Window Detection
- Local control through control panel
- Temperature control from 5°C to 40°C
- Adjustable power output from 100W to max
- Low-temperature panel heater with a maximum surface temperature of 58°C
- Overheat protection
- Tip-over protection
- Child lock
- Splash proof (IP24)
- Firmware update (OTA)
- Wall bracket
- Wide range of outputs
- White or black color

PRODUCT DATA

Voltage	230VAC
Grounding	Yes
Total gross effect	1500W
Max surface temperature	58°C
Cold lead	1.3m
Indicative heating area	20 to 24m²
Ambient temperature range in use	5 to 40°C
Ambient temperature range in storage (°C)	-30 to 70°C
Min. and max ambient humidity (RH%)	10 to 85%
Material	Steel
Colour	Black
Mounting	Freestanding With legs, Mounted with bracket
Depth with bracket	8cm
IP Code	IP24
Certification	Reach, RoHS
EN Standards	CE
Warranty international	5 years
Customs number	85162901

PRODUCT DIMENSIONS

Product length	1000mm	Product width	430mm
Product height-/depth	65mm	Product net weight	6400g

MAINTENANCE

Indoor use only.

Cleaning:
Switch off and unplug from the power supply before cleaning.
• Using a soft, moist cloth, with or without a mild soap solution, carefully clean the exterior surface of the product.
• CAUTION: Allow the product to completely cool before handling or cleaning it.
• Do not allow water or other liquids to run into the interior of the product, as this could create a fire and/or electrical hazard.
• We also recommend the periodic cleaning of this appliance by lightly running a vacuum cleaner nozzle over the guards to remove any dust or dirt that may have accumulated inside or on the unit.
• CAUTION: Do not use harsh detergents, chemical cleaners or solvents as they may damage the surface finish of the plastic components.

ADDITIONAL INFORMATION

Downtime related to the app or cloud/service platform is not covered by the warranty.

White cold lead to white panel heater and black cold lead to black panel heater.

RETURN AND RECYCLING

The product must be recycled as electronic waste.

HEATIT CABLE DATA

Cold lead	1.3m	Indicative heating area	20 to 24m^2

DISCLAIMER

If you encounter an error code try turning off the power to the panel heater, either by using the main switch or unplugging the cord, to reset the device.

We develop and design our products according in accordance with our strict quality requirements (ISO 9001) and environmental requirements (ISO 14001).
All electrical installations must be carried out by an authorized electrical installer. The product must be installed in accordance with our installers manual and national building codes. Any wrongful installation, misuse, damage of the product, is not covered under warranty.

Updated documentation is available at www.heatit.com or documents.heatit.com
Heatit Controls AS can not be held liable for any type of errors or omittances in our product information.
Product specifications may change without further notice.

Heatit Controls AS
Mattisrudsvingen 19, 2827 Hunndalen, Norway
Tel: +47 61 18 77 77 | post@heatit.com
heatit.com | **documents.heatit.com**

Designed in Norway
RoHS Compliant
REACH Compliance
CE