

HEATIT WIFI PANEL HEATER 1500W BLACK GLASS 1020X425MM

Electrical Radiator WiFi. Glass front.

Art.no	5430510
GTIN	7071236020042

Smart panel heater. The Heatit WiFi Panel Heater combines modern design, energy-efficient heating and smart temperature control to provide comfortable heating in residential and commercial environments.
The panel heater connects easily to your Wi-Fi network, allowing you to control and monitor the heating through the "MyHeatit" App, wherever you are. Turn the heater on or off, adjust the temperature, switch between heating modes and monitor energy consumption directly from your smartphone.

The Heatit WiFi Panel Heater features two operating modes: Heat and Eco, allowing you to balance comfort and energy savings. The heater can also be controlled using the integrated buttons on top of the unit or through compatible third-party systems using its open API over Wi-Fi. It also supports Amazon Alexa and Google Home.

Design and installation
The Heatit WiFi Panel Heater features a slim, modern design that blends naturally into different interior environments. Standard panel heaters are available with either a steel or glass front, while low-profile panel heaters are available with a steel front.
The panel heater is easy to install using the supplied wall-mounting bracket. Alternatively, it can be installed on optional metal feet, sold separately (Art. no. 54 305 12).

Safety and comfort
The Heatit WiFi Panel Heater is designed as a low-temperature heater, with a maximum surface temperature of 58°C. This makes it particularly suitable for environments where safety and comfort are important, such as kindergartens, schools and other public or residential areas.
With its modern design and IP24 rating, the Heatit WiFi Panel Heater is suitable for installation in living rooms, bedrooms and bathrooms. In bathrooms, the heater must be installed in Zone 2, in accordance with applicable national electrical regulations and installation requirements.
For added safety, the heater is equipped with built-in tip-over protection, which automatically disconnects the heating if the unit tips over.

Installer setup and customer handover
The Heatit WiFi Panel Heater supports Bluetooth configuration, allowing installers to set up the device without connecting it to a Wi-Fi network. Once configured, the installer can assign the device to the customer's property. The customer can then connect the heater to their local Wi-Fi network and manage it through the "MyHeatit" App. This provides a simple and efficient installation process, from initial configuration to final customer handover.

Product range
Heatit WiFi Panel Heaters are available in two versions:
* Standard panel heaters – Available with steel or glass fronts.
* Low-profile panel heaters – Available with steel fronts.

Depending on the model, the heaters are available in white or black, with power outputs ranging from 400W to 1500W.

PRODUCT FEATURES

- Wi-Fi (2.4GHz)/BLE
- Open API for integration
- Digital thermostat
- Silent control Triac
- Easy-to-read LCD display
- Two modes: Heat and Eco-mode
- Active power metering
- Open Window Detection
- Local control through control panel
- Temperature control from 5°C to 40°C
- Adjustable power output from 100W to max
- Low-temperature panel heater with a maximum surface temperature of 58°C
- Overheat protection
- Tip-over protection
- Child lock
- Splash proof (IP24)
- Firmware update (OTA)
- Wall bracket
- Wide range of outputs
- White or black color

PRODUCT DATA

Voltage	230VAC
Grounding	Yes
Total gross effect	1500W
Max surface temperature	58°C
Cold lead	1.3m
Indicative heating area	20 to 24m^2
Ambient temperature range in use	5 to 40°C
Ambient temperature range in storage (°C)	-30 to 70°C
Min. and max ambient humidity (RH%)	10 to 85%
Material	Glass, Steel
Colour	Black
Mounting	Freestanding With legs, Mounted with bracket
Depth with bracket	8cm
IP Code	IP24
Certification	Reach, RoHS
EN Standards	CE
Warranty international	5 years

PRODUCT DIMENSIONS

Product length	1020mm	Product width	425mm
Product height-/depth	63mm	Product net weight	8500g

MAINTENANCE

Indoor use only.

Cleaning:
Switch off and unplug from the power supply before cleaning.
• Using a soft, moist cloth, with or without a mild soap solution, carefully clean the exterior surface of the product.
• CAUTION: Allow the product to completely cool before handling or cleaning it.
• Do not allow water or other liquids to run into the interior of the product, as this could create a fire and/or electrical hazard.
• We also recommend the periodic cleaning of this appliance by lightly running a vacuum cleaner nozzle over the guards to remove any dust or dirt that may have accumulated inside or on the unit.
• CAUTION: Do not use harsh detergents, chemical cleaners or solvents as they may damage the surface finish of the plastic components.

ADDITIONAL INFORMATION

Downtime related to the app or cloud/service platform is not covered by the warranty.

White cold lead to white panel heater and black cold lead to black panel heater.

RETURN AND RECYCLING

The product must be recycled as electronic waste.

HEATIT CABLE DATA

Cold lead	1.3m	Indicative heating area	20 to 24m^2

DISCLAIMER

If you encounter an error code try turning off the power to the panel heater, either by using the main switch or unplugging the cord, to reset the device.

We develop and design our products according in accordance with our strict quality requirements (ISO 9001) and environmental requirements (ISO 14001).
All electrical installations must be carried out by an authorized electrical installer. The product must be installed in accordance with our installers manual and national building codes. Any wrongful installation, misuse, damage of the product, is not covered under warranty.

Updated documentation is available at www.heatit.com or documents.heatit.com
Heatit Controls AS can not be held liable for any type of errors or omittances in our product information.
Product specifications may change without further notice.

Heatit Controls AS
Mattisrudsvingen 19, 2827 Hunndalen, Norway
Tel: +47 61 18 77 77 | post@heatit.com
heatit.com | **documents.heatit.com**

Designed in Norway
RoHS Compliant
REACH Compliance
CE