



HEATIT QUICKMAT DECOUPLING 15M2

Decoupling Mat with fleece - Roll

Art.no	1011228
GTIN	7071236020073

Heatit QuickMat – Decoupling Membrane System

Heatit QuickMat is a decoupling membrane system designed for fast and reliable installation of electrical floor heating. The membrane separates the heating system and tile covering from the subfloor, reducing the risk of cracks caused by movement, expansion, or tension in the substrate.

The membrane is installed directly onto a prepared subfloor that is clean, dry, and free from dust and debris. Once fixed to the surface using suitable tile adhesive, the heating cable is easily pressed into the membrane's stud structure according to the planned cable spacing. This ensures correct cable positioning and even heat distribution across the floor area.

Heatit QuickMat is designed to be used together with Heatit GVK, BVK, and RVK heating cables. The membrane keeps the heating cable securely in place without the need for additional fixing tools, allowing a quick and flexible installation.

After the heating cable is installed, the membrane and cable are covered with tile adhesive or leveling compound before installing the final floor covering. The system is suitable for use under tile, natural stone, and other floor coverings approved for electrical floor heating.

PRODUCT FEATURES

- Suitable for installation on concrete, leveling compound, chipboard, and when renovating wooden floors or tiled surfaces. It can replace gypsum boards and masterboard, while the pre-made grooves for 3.5mm heating cable ensure correct cable spacing and make installation quick and easy. The solution also helps protect the floor against cracking caused by movement in the subfloor. The fleece-coated underside provides strong adhesion to tile adhesive. Supplied in rolls of 15m² (1x15m), with a low build-up height of only 6mm.

PRODUCT DATA

Covering	Tiles Slate Carpet floor Laminate floors Vinyl Parquet floors
Material	Polypropylene (PP)
Colour	Red

ADDITIONAL INFO

Warranty international	2 years
------------------------	---------

HEATING CABLE SUBSTRATE DATA

Board size (WxL in meters)	1x15
Sheet Thickness	6mm
Covered area per package (m ²)	15m ²

**PRODUCT DIMENSIONS**

Product height/diameter	6mm	Product Width	1000mm
Product length	15000mm	Product net weight	250g

MAINTENANCE

No maintenance.

RETURN AND RECYCLING

Must be delivered as plastic waste to an approved waste reception or recycling station.
Normally sorted as rigid plastic / plastic from building materials.
Must not be disposed of as residual (general) waste.

DISCLAIMER

All electrical installations must be carried out by an authorized electrical installer and the system must be installed in accordance with the installer's manual and national building regulations.



Heatit QuickMat Decoupling 15m2 can be ordered from www.thermo-floor.no/1011228

All additional documentation are available on the above adress and on documents.heatit.no/1011228

