

TEC-BOND 23/12/300 1 KG

Hotmelt glue - 1kg

Art.no	8811320
GTIN	7071236004806

Versatile hot melt adhesive for assembly and fixing

Tecbond 23 is a professional EVA-based hot melt adhesive developed for a wide range of assembly, installation and repair applications. The adhesive provides good adhesion to a variety of common materials and combines good working time with rapid bonding as it cools.

Its high viscosity provides good gap-filling properties, making Tecbond 23 well suited for general assembly, fixing of heating cables and use on uneven surfaces. The adhesive is easy to apply and provides fast, efficient and reliable fixing.

PRODUCT FEATURES

- Suitable for uneven surfaces.
- Colour: Pale amber
- EVA-based hot melt adhesive.
- Open time: Approx. 30 seconds
- Technical data
- Softening point: Approx. 88°C
- Chemical base: EVA
- Heat resistance: Up to 80°C
- Versatile assembly adhesive for a wide range of applications.
- Especially well suited for fixing heating cables.
- Fast and efficient for both spot fixing and full-surface bonding.
- Good working time for positioning and adjustment.
- Good adhesion to many common materials.
- High viscosity with good gap-filling properties.
- Rapid bonding as the adhesive cools.
- Suitable for production, installation and repair applications.
- Application temperature: 180–195°C
- Viscosity: Approx. 5,000 cPs at 180°C
- Minimum recommended service temperature: 0°C
- Always test the adhesive on the actual materials before use and compare the results with other adhesive types to ensure optimal adhesion and suitability.

ADDITIONAL INFO

Certification	Reach, RoHS

PRODUCT DIMENSIONS

Product length	290mm	Product Width	190mm
Product height/diameter	35mm	Product net weight	1000g

MAINTENANCE

No need for maintenance.

RETURN AND RECYCLING

Recycle as plastic materials.

HOTMELT GLUE DATA

Glue stick/cartridge Ø	12mm limstav	Quantity glue stick/cartridge approx.	33
Open time (seconds)	30s		

DISCLAIMER

We develop and design our products according in accordance with our strict quality requirements (ISO 9001) and environmental requirements (ISO 14001).
All electrical installations must be carried out by an authorized electrical installer. The product must be installed in accordance with our installers manual and national building codes. Any wrongful installation, misuse, damage of the product, is not covered under warranty.

Updated documentation is available at www.heatit.com or documents.heatit.com
Heatit Controls AS can not be held liable for any type of errors or omittances in our product information.
Product specifications may change without further notice.